

# Product Information Sheet



## FPS Aboveground Storage Tank (AST) Treatment (Product # 50030)

***FPS AST Treatment*** is specifically formulated for Ultra Low Sulfur Diesel (ULSD) subjected to ambient temperatures below the fuel's cloud point for extended periods of time, as typically experienced with fuel stored and dispensed from aboveground tanks in the winter months.

***FPS AST Treatment*** is designed to minimize the settling of wax particles that can come out of solution at the cloud point. This performance is achieved by formulating with a Wax Anti Settling Agent (WASA). This product is also enhanced with a robust level of deicer to treat moisture that is often condensed due to the wide temperature swings that are encountered with AST(s). This product should be used in conjunction with winter fuel treatments such as FPS Premium Winter.

### Benefits:

- ✓ Minimizes wax settling in Low and Ultra Low Sulfur Diesel Fuels
- ✓ Helps to prevent wax particles from clogging fuel system supply lines and fuel filters
- ✓ Provides up to 18°F depression as measured in the ASTM D4539— "Filterability of Diesel Fuels by Low-Temperature Flow Test (LTFT)
- ✓ Disperses up to 100 PPM of water and keeps it from freezing
- ✓ Contains no harmful alcohols
- ✓ Enhances the performance of FPS Premium Winter in situations where the fuel is subject to harsher and more severe cold weather conditions

### Recommended Treatment Ratio:

One gallon of ***FPS AST Treatment*** conditions 1000 gallons of diesel fuel.